Revision & Date: HUXSFA30103

FAInspectorTM

Fiber Array (End-face) Inspector

Special Features

- Very usefully device to inspect Fiber Array End-face
- · Easy operation and Portable Type
- Wide 5.6" TFT LCD Monitor
- · Low Price but good capacity
- · Foldable Monitor and adjustable Angle
- Easy charging by AC 110/220V
- · Save Data on PC by USB device
- Brightness & Contrast adjustable
- · Anti-slip design and Easy Focus
- Complied with RoHS/CE
- USB Computer or CRT Monitor available



Specifications

Brand Name		FAInspector
Magnification		260X by 5.6" LCD, 400X by USB or 9" CRT Monitor
Filed of Vision		400um x 300um
Vidual Capacity		Upto 32-channel
Focus		Manual, Maximum 2mm in and out
CCD		1/3" Sony CCD sensor
Battery & Power Supply		9.6V 2700mA NH-AA Rechargeable Battery, AC adaptor
USB device (Option)		Video Capture Device with Software for Windows 98/2000/XP
CRT Monitor Interface Cable (Option)		DIN or BNC or RCA available
Dimension	Main Body	11.3cm(W) x 28cm(L) x 6.2cm (H), Weight 1.3kg
	Monitor (when folded)	150mm (W) x 125mm (D) x 52mm (H)
Video Output		NTSC (default) or PAL

Standard Package

P/N: FAInspector

- 1 Main Body (standard 0° Angle Fiber Array) included Handset
- 1 LCD 5.6" Monitor
- 1 Rechargeable Battery Pack
- 1 DIN Cable
- 1 AC Power Adaptor / Battery Charger
- 1 Manual
- 1 Package

[Option] 1. Holder for 8° Angle Fiber Array could be added.

2. USB Device with Software and/or CRT Monitor Interface Cable could be added



Manufacturer: TheFibers Inc.

A-1109 Keumkang Penterium IT Tower, 282 Hagui-ro, Anyang-City, Korea Tel: +82-31-381-6108 Fax: +82-31-381-6109 sales@thefibers.com